

# Advance Security



## 4 HD Armor Dome Camera Security Package

Indoor Outdoor HD color dome cameras, 4 cables, and standalone HD 1080p DVR

Part Numbers: PKG-4ADHDIR, PKG-4ADHDIR2TB

<http://www.surveillance-spy-cameras.com/4-dome-camera-dvr-package.htm>

### Specifications

#### Camera Specifications

SSC-DIR-ARG28	Grey HD Dome Camera Fixed Lens 2.8mm
SSC-DIR-ARG28	White HD Dome Camera Fixed Lens 2.8mm
Image Sensor	CMOS 2.4MP
Effective Pixels	1920(H) x 1080(V)
Electronic Shutter	NTSC: 1/60s-1/10000s
S/N Ratio	> 48 dB
OSD Menu	No
Min. Illumination	0 Lux (with IR LED On)
Video Output	AHD/CVI/TVI/CVBS 1080p
IR LEDs	24
Max. IR LEDs Distance	65ft (20m)
Day/Night	Yes
IP Rating	IP66
IR Status	Under 10 Lux by CDS
Lens Focal Length	2.8mm
Power Supply	DC12V
Power Consumption	300mA
Working Environment	-22°F ~ +140°F (-30°C ~ +60°C)
Dimensions	3.7x2.75in (94x70mm)
Weight	0.75lb (357g)
Warranty	1 Year Warranty

#### DVR Specifications

HDD	One (1) SATA Port, up to 6 TB capacity
Video System	LINUX
Video Compression Format	Smart H.264+/H.264
Video Input	Supports HDCVI/AHD/TVI/CVBS/IP Video Inputs
Resolution	1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768
Audio Input / Output	4 Channels/1 Channel
Record Rate	Main Stream: 1080p (1 to 15 fps) or 1080N/720p/960H/D1/HDI/BCIF/CF/CCIF (1 to 25/30 fps)
Recording Mode	Manual, Schedule (Regular, Continuous), Motion Detection (Video Detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Display Interface	1 HDMI 1 VGA
USB Port	2 x USB 2.0 Ports
Network Interface	RJ-45 Port (100 M)
Power Source	DC12V / 2 A
Power Consumption	< 10 W (without HDD)
Operating Temperature	-10°C to +55°C (+14°F to +131°F), 86 to 106 kpa
Dimension	(W x H x D) 12.80 in. x 10.0 in. x 2.20 in
Weight	1.50 kg (3.30 lbs), without HDD
Warranty	3 Years

### Package Includes