

Advance Security



8 HD Varifocal Camera with DVR Package

Complete HD DVR package with 8 weatherproof varifocal cameras

Part Numbers: PKG-8VFHDIR, PKG-8VFHDIR4TB

<http://www.surveillance-spy-cameras.com/8-camera-package-with-dvr.htm>

Specifications

Specifications

Camera	SSC-HD-IR2812VFBG Grey
Camera	SSC-HD-IR2812VFBW White
Image Sensor	CMOS 2.4MP
Effective Pixels	1920(H) x 1080(V)
S/N Ratio	> 48 dB
Min. Illumination	0 Lux (with IR LED On)
Video Output	AHD/CVI/TVI/CVBS
IR LED Unit	30
Max. IR LEDs Length	130ft (40m)
Day/Night	Yes
IP Rating	IP66
IR Status	Under 10 Lux by CDS
Lens Focal Length	2.8~12mm
Power Supply	DC12V
Power Consumption	400mA
Working Environment	-22°F ~ +140°F (-30°C ~ +60°C)
Dimensions	9.45(L)x3.94(W)x3.94(H) / 240(L)x100(W)x100(H)mm
Weight	2.2lb (1000g)
Warranty	1 Year

Specifications

DVR-HD8CH	2TB Model
DVR-HD8CH4TB	4Tb Model
Video Input	4/ 8 / 16CH
Video Output	HDMIx1, VGAx1(1920x1080, 1280x1024, 1280x720, 1024x768)
Audio Compression	H.264+ / H.264
Audio Output	1 Output
Audio Input	8 Inputs
Backup Mode	USB Device; Network
HD Camera Input	4/8/16 Channels
Interface	One (1) HDMI, one (1) VGA
Internal HDD	1 SATA port, up to 6TB HDD
IP Camera Input	4+2/8+4/16+8 Channels, each channel up to 5 MP
Multi-screen Display	4 Ch: 1/4/6; 8 Ch: 1/4/8/9/16; 16 Ch: 1/4/8/9/16/25
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Playback	4 Ch: 1/4; 8 Ch: 1/4/9; 16 Ch: 1/4/9/16
USB	4 Ch: Two (2) USB 2.0 Ports; 8/16 Ch: One (1) USB 2.0 One (1) USB 3.0 Port
Power Source	DC12V 2A
Power Consumption	10W(No HDD)
Operating Temperature	-10°C ~ +55°C / 10%~90%RH / 86~106kpa
Dimension	(W x H x D) 12.7" x 10" x 2.1"
Weight	1.45KG(No HDD)
Warranty	3 Year

Package Includes

- 8 ea. SSC-HD-CVI-IR2812VFBW Adjustable Lens HD IR Cameras
- 8 ea. CA-50 50ft Power Video Cables
- 1 ea. HD-DVR8CVI 8 Channel High Definition HDCVI/Standard DVR
- 8 ea. 1 amp power supplies